



DIN 7991 / ISO 10642

INOX A4



Dimensions	M3	M4	M5	M6	M8	M10	M12	M16	M20	M24
S	2	2.5	3	4	5	6	8	10	12	14
K.max	1.7	2.3	2.8	3.3	4.4	5.5	6.5	7.5	8.5	14
dK	6	8	10	12	16	20	24	30	36	39
PAS	0.5	0.7	0.8	1	1.25	1.5	1.75	2	2.5	3
Fraisage	90°	90°	90°	90°	90°	90°	90°	90°	90°	60°

L/D	M3	M4	M5	M6	M8	M10	M12	M16	M20	M24
6	○	○	○							
8	○	○	○	○						
10	○	○	○	○	○					
12	○	○	○	○	○					
14	○	○	○	○	○					
16	○	○	○	○	○	○				
18	○	○	○	○	○					
20	○	○	○	○	○	○	○			
22										
25	○	○	○	○	○	○	○	○		
30	○	○	○	○	○	○	○	○		
35										
40	○									
45										
50		○							○	
55			○						○	○
60			○						○	○
65				○						
70				○	○	○	○	○	○	○
75										
80				○	○	○	○	○	○	○
85										
90				○	○	○	○	○	○	○
100				○	○	○	○	○	○	○
110										
120					○	○	○	○	○	○
130										
140								○	○	○
150								○	○	○