

COLLIER DE SERRAGE THERMIQUE 19 MM EN ACIER ZINGUÉ


PARAMETRES D'INSTALLATION

CODE	Ø D	B2	M	A1 x B1	A2	C	Plage de fixation D	Charge maximale recommandée
							[mm]	[kg]
ABAIS19010	10	19	M8/M10	25 x 1,5	25	17	27-28	150
ABAIS19012	12	19	M8/M10	25 x 1,5	25	17	10-12	150
ABAIS19015	15	19	M8/M10	25 x 1,5	25	17	15 -16	150
ABAIS19017	17	19	M8/M10	25 x 1,5	25	17	17	150
ABAIS19018	18	19	M8/M10	25 x 1,5	25	17	17 - 18	150
ABAIS19022	22	19	M8/M10	25 x 1,5	25	17	21 - 22	150
ABAIS19028	28	19	M8/M10	25 x 1,5	25	17	27 - 28	150
ABAIS19035	35	19	M8/M10	25 x 1,5	25	17	35	150
ABAIS19042	42	19	M8/M10	25 x 1,5	25	17	42	150
ABAIS19054	54	19	M8/M10	25 x 1,5	25	17	54	150
ABAIS19060	60	19	M8/M10	25 x 2,0	25	17	60	150
ABAIS19064	64	19	M8/M10	25 x 2,0	25	17	64	150
ABAIS19067	67	19	M8/M10	25 x 2,0	25	17	67	150
ABAIS19076	76	19	M8/M10	25 x 2,0	25	17	76	150
ABAIS19080	80	19	M8/M10	25 x 2,0	25	17	80	150
ABAIS19114	114	19	M8/M10	25 x 2,0	25	17	114	150

MATÉRIAUX :



tube acier



tube cuivre



tube PVC



tube ventilation

* AUTRES DIMENSIONS NOUS CONTACTER contact@visserie-sabf.fr ou au [02.40.49.94.83](tel:02.40.49.94.83)