


## COLLIER DE SERRAGE THERMIQUE 30 MM EN ACIER ZINGUÉ

### PARAMETRES D'INSTALLATION

CODE	Ø D	B2	M	A1 x B1	A2	C	Plage de fixation D	Charge maximale recommandée
							[mm]	[kg]
<b>ABAIS30027</b>	27	30	M8/M10	25 x 2,0	25	17	27 - 28	150
<b>ABAIS30034</b>	34	30	M8/M10	25 x 2,0	25	17	34 - 35	150
<b>ABAIS30042</b>	42	30	M8/M10	30 x 2,0	30	17	42	150
<b>ABAIS30049</b>	49	30	M8/M10	30 x 2,0	30	17	49	150
<b>ABAIS30054</b>	54	30	M8/M10	30 x 2,0	30	17	54	150
<b>ABAIS30060</b>	60	30	M8/M10	30 x 2,0	30	17	60	150
<b>ABAIS30076</b>	76	30	M8/M10	30 x 2,0	30	17	76	150
<b>ABAIS30089</b>	89	30	M8/M10	30 x 2,0	30	17	88,9	150
<b>ABAIS30108</b>	108	30	M8/M10	40 x 4,0	40	17	108	200
<b>ABAIS30114</b>	114	30	M8/M10	40 x 4,0	40	17	114	200

### MATÉRIAUX :



tube acier



tube cuivre



tube PVC



tube ventilation

\* AUTRES DIMENSIONS NOUS CONTACTER [contact@visserie-sabf.fr](mailto:contact@visserie-sabf.fr) ou au [02.40.49.94.83](tel:02.40.49.94.83)