



COLLIER DE SERRAGE ISOPHONIQUE RENFORCÉ GLISSANT M8 + M10 EN ACIER ZINGUÉ

PARAMETRES D'INSTALLATION

CODE	Ø D	A x B	C	Plage de fixation D	Charge maximale recommandée
	[mm]	[mm]	[mm]		
ABRID016	16	20 x 1,2	17	16 - 19	40
ABRID020	20	20 x 1,2	17	20 - 23	40
ABRID025	25	20 x 1,2	17	25 - 30	40
ABRID032	32	20 x 1,2	17	31 - 36	40
ABRID040	40	20 x 1,2	17	40 - 46	40
ABRID050	50	20 x 1,5	17	48 - 53	80
ABRID063	63	20 x 1,5	17	60 - 65	80
ABRID075	75	20 x 1,5	17	72 - 78	80
ABRID090	90	20 x 1,5	17	87 - 92	80
ABRID110	110	20 x 2,0	17	105 - 115	180
ABRID125	125	20 x 2,0	17	124 - 130	180
ABRID140	140	20 x 2,0	17	135 - 145	180
ABRID160	160	20 x 2,0	17	160 - 168	180

MATÉRIAUX :



tube acier



tube cuivre



tube PVC



tube ventilation

* AUTRES DIMENSIONS NOUS CONTACTER contact@visserie-sabf.fr ou au [02.40.49.94.83](tel:02.40.49.94.83)