



COLLIER DE SERRAGE THERMIQUE 40 MM EN ACIER ZINGUÉ

PARAMETRES D'INSTALLATION

| CODE | Ø D | B2 | M | A1 x B1 | A2 | C | Plage de fixation D | Charge maximale recommandée |
|-------------------|-----|----|---------|----------|----|----|---------------------|-----------------------------|
| | | | | | | | [mm] | [kg] |
| ABAIS40049 | 49 | 40 | M8/M10 | 30 x 3,0 | 30 | 17 | 49 | 200 |
| ABAIS40060 | 60 | 40 | M8/M10 | 40 x 4,0 | 40 | 17 | 60 | 200 |
| ABAIS40089 | 89 | 40 | M8/M10 | 40 x 4,0 | 40 | 17 | 89 | 200 |
| ABAIS40114 | 115 | 40 | M8/M10 | 40 x 4,0 | 40 | 17 | 115 | 200 |
| ABAIS40133 | 133 | 40 | M8/M10 | 40 x 4,0 | 40 | 17 | 133 | 200 |
| ABAIS40140 | 140 | 40 | M8/M10 | 40 x 4,0 | 40 | 17 | 140 | 200 |
| ABAIS40159 | 159 | 40 | M12/M16 | 40 x 4,0 | 40 | 17 | 159 | 200 |
| ABAIS40168 | 168 | 40 | M12/M16 | 40 x 4,0 | 40 | 17 | 168 | 200 |
| ABAIS40219 | 219 | 40 | M12/M16 | 40 x 4,0 | 40 | 17 | 219 | 200 |

MATÉRIAUX :



tube acier



tube cuivre



tube PVC



tube ventilation

* AUTRES DIMENSIONS NOUS CONTACTER contact@visserie-sabf.fr ou au [02.40.49.94.83](tel:02.40.49.94.83)