


## COLLIER RENFORCÉ M8 OUVERT EN ACIER ZINGUÉ

### PARAMETRES D'INSTALLATION

CODE	Dimensions	Ø D	Ø D	A x B	Charge maximale recommandée
	[mm]	[mm]	["]	[mm]	
ABRA015	15	12-16	1/4"	20x1,5	80
ABRA018	18	15 - 19	3/8"	20x1,5	80
ABRA022	22	20 - 25	1/2"	20x1,5	80
ABRA028	28	26 - 30	3/4"	20x1,5	80
ABRA035	35	32 - 36	1"	20x1,5	80
ABRA042	42	38 - 43	1 1/4"	20x1,5	80
ABRA048	48	47 - 51	1 1/2"	20x1,5	80
ABRA054	54	53 - 58	-	20x1,5	80
ABRA060	60	60 - 64	2"	20x1,5	80
ABRA075	75	75 - 80	2 1/2"	20x1,5	80
ABRA090	90	87 - 92	3"	20x1,5	80
ABRA100	100	99 - 105	3 1/2"	20x1,5	80
ABRA110	110	107 - 112	-	20x1,5	80
ABRA115	115	113 - 118	4"	20x1,5	80
ABRA125	125	125 - 130	4 1/2"	20x1,5	80

**MATÉRIAUX :**



tube acier



tube cuivre



tube PVC



tube ventilation