



COLLIER RENFORCÉ ISOPHONIQUE M8 + M10 EN ACIER ZINGUÉ

PARAMETRES D'INSTALLATION

CODE	Dimensions	Ø D	Ø D	A x B	Charge maximale recommandée
	[mm]	[mm]	["]	[mm]	
ABRI018	18	15 - 19	3/8"	18.5x1.75	150
ABRI022	22	20 - 25	1/2"	18.5x1.75	150
ABRI028	28	26 - 30	3/4"	18.5x1.75	150
ABRI035	35	32 - 36	1"	18.5x1.75	150
ABRI040	40	38 - 43	1 1/4"	18.5x1.75	150
ABRI048	48	47 - 51	1 1/2"	18.5x1.75	150
ABRI054	54	53 - 56	-	18.5x1.75	150
ABRI060	60	60 - 64	2"	18.5x1.75	150
ABRI070	70	68 - 72	-	18.5x1.75	150
ABRI075	75	75 - 80	2 1/2"	18.5x1.75	150
ABRI083	83	81 - 86	-	18.5x1.75	150
ABRI090	90	87 - 92	3"	18.5x1.75	150
ABRI100	100	99 - 105	3 1/2"	18.5x1.75	150
ABRI110	110	107 - 112	-	18.5x2,3	200
ABRI115	115	113 - 118	4"	18.5x2.3	200
ABRI125	125	125 - 130	4 1/2"	18.5x2,3	200
ABRI133	133	132 - 137	-	18.5x2.3	200
ABRI140	140	138 - 142	5"	18.5x2,3	200
ABRI150	150	148 - 152	-	18.5x2.3	200

* AUTRES DIMENSIONS NOUS CONTACTER contact@visserie-sabf.fr ou au [02.40.49.94.83](tel:02.40.49.94.83)

PARAMETRES D'INSTALLATION

CODE	Dimensions	Ø D	Ø D	A x B	Charge maximale recommandée
	[mm]	[mm]	["]	[mm]	
ABRI160	160	159 - 166	6"	18.5x2,3	200
ABRI180	180	179 - 184	8"	18.5x2,3	200
ABRI200	200	199 - 212	-	18.5x2,3	200
ABRI220	220	215 - 226	-	18.5x2,3	200
ABRI250	250	245 - 254	-	18.5x2,3	200
ABRI300	300	299 - 304	-	18.5x2,3	200
ABRI315	315	314 - 319	-	18.5x2,3	200
ABRI355	355	354 - 359	-	18.5x2,3	200
ABRI400	400	399 - 404	-	18.5x2,3	200
ABRI450	450	449 - 454	-	18.5x2,3	200
ABRI500	500	499 - 504	-	18.5x2,3	200
ABRI560	560	555 - 561	-	18.5x2,3	200
ABRI600	600	599 - 604	-	18.5x2,3	200
ABRI630	630	625 - 631	-	18.5x2,3	200
ABRI710	710	705 - 711	-	18.5x2,3	200
ABRI800	800	799 - 804	-	18.5x2,3	200
ABRI900	900	899 - 904	-	18.5x2,3	200
ABRI910	1000	999 - 1.004	-	18.5x2,3	200
ABRI911	1120	1.115 - 1.121	-	18.5x2,3	200
ABRI912	1250	1.245 - 1.251	-	18.5x2,3	200

MATÉRIAUX :



tube acier



tube cuivre



tube PVC



tube ventilation

* AUTRES DIMENSIONS NOUS CONTACTER contact@visserie-sabf.fr ou au [02.40.49.94.83](tel:02.40.49.94.83)